


NEC MultiSync® M551 PG-2
LCD 55" Protective Glass Large Format Display

Datasheet



Meticulously Powerful Signage with Professional Protection

The NEC MultiSync® M551 PG-2 combines professional protection of your investment with unparalleled display performance. Deliver your message with impact and seamless simplicity for the most convincing results.

Guaranteed reliability even under the toughest conditions is achieved with the super robust 4mm thick protective glass designed to withstand external impacts. The anti-reflective glass surface combined with brightness levels of 500 cd/m² provides crisp and clear images and readability from different viewing angles and distances.

The MultiSync® M551 PG-2 is the perfect choice for creating a big and durable impression in public spaces with high volumes of people such as for applications in transportation, retail, hospitality and digital out of home as well as for tough environments in industrial applications.

Benefits

Maximum investment security – assured as the display is protected against damage from external impacts such as knocks and blows.

Protects the public – the thermally toughened protective glass will disintegrate into small fragments reducing the risk of injury should it suffer extreme damage.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Superb readability – supported through the use of anti-reflective and high light-transmission GroGlass® protective glass.

Product Information

Product Name	NEC MultiSync® M551 PG-2
Product Group	LCD 55" Protective Glass Large Format Display
Order Code	60005852

Display

Panel Technology	IPS with Edge LED backlights
Aspect Ratio	16:9
Brightness [cd/m ²]	500
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	8
Supported Orientation	Landscape; Portrait

Glass

Type	GroGlass® Protective Glass
Thickness [mm]	4
Light Transmission [%]	≥ 97
Reflection Rate [%]	1

Resolution

Native Resolution	3840 x 2160
Supported Resolutions	1024 x 768; 1366 x 768; 1650 x 1050; 2560 x 1600; 1280 x 1024; 1440 x 900; 1900 x 1200; 3840 x 2160; 1360 x 768; 1600 x 1200; 2560 x 1440; 4096 x 2160

Synchronisation Rate

Horizontal Frequency [kHz]	26 - 91.1
----------------------------	-----------

Connectivity

Input Video Digital	1 x DisplayPort (with HDCP)
Input Audio Digital	1 x DisplayPort
Input Control	LAN 100Mbit; remote control wire (3,5mm jack); RS232
Input Data	1 x USB 2.0 (MediaPlayer)
Output Audio Analogue	1 x 3,5 mm jack
Input Detect	Custom; First; Last

Open Modular Intelligence

Intel® SDM	accepts Intel® Smart Display Modules Large and Small up to 66 W
Compute Module Slot	RPI Compute Module 4

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
----------------------	--------------------------------------------

Electrical

Power Consumption Eco/max. [W]	110 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS
Power Supply	internal

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90

Mechanical

Weight [kg]	38.5
Bezel Width [mm]	16 (top); 19.6 (bottom); 22.1 (left and right)
VESA Mounting [mm]	300 x 300 (FDMI); 4 holes
Packaging Dimensions (W x H x D) [mm]	1,430 x 920 x 250
Packaging Weight [kg]	48.6

MediaPlayer

Supported File Storage / File System	USB 2.0 / FAT16, FAT32
Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640
Supported Video Formats	MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)

Available Options

Accessories	Feet (ST-43M); Presence Sensor (KT-RC3); Soundbar (active: SP-ASCM-IQ2 / SP-ASCM-2); Speaker (SP-RM3a); Trolley (PD04-Tipster Trolley); Wall mount (PDW S 32-65 L, PDW S 32-65 P)
-------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Green Features

Energy Efficiency	Energy efficiency class: G; LED backlight
Ecological Standards	EnergyStar 8.0

Additional Features

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
Safety and Ergonomics	BSMI; CE; EAC; EMC Class B; FCC Class B; RCM; VCCI
Pixel Failure Class	ISO 9241-307, Class 1
Shipping Content	HDMI Cable; Power Cable; Remote Control; Setup Manual
Warranty	additional services available; optional 4. + 5. year warranty extension ¹
Operating Hours	24/7
External Control	AMX NetLinx Support; ASCII Control Commands; Crestron Connected; HDMI CEC; PJLink; SNMP
Remote Management	Automated Email Alerts; NEC NaViSet Administrator 2
Security	Disable HW Buttons; Disable IR Functionality; Emergency Notification

¹ please refer to terms and conditions of warranty extensions



RCM



VCCI



FCC Class B



CE

This document is © 2023 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 04.08.2023